



Borough of Palisades Park

275 Broad Avenue
Bergen County, N.J. 07650

Building Department
Tel: (201) 585-4108
Fax: (201) 585-4110

APPLICATION ONLY

Building Department

Application for New Home Certificate

This Application is NOT VALID Until ALL information is provided

PROPERTY LOCATION: _____

CURRENT OWNER'S NAME: _____ **PHONE #:** _____

CURRENT OWNER'S ADDRESS: _____

CURRENT OWNER'S EMAIL: _____

BUYER'S NAME: _____ **PHONE #:** _____

BUYER'S CURRENT ADDRESS: _____

BUYER'S ATTORNEY INFO:	SELLER'S ATTORNEY INFO:
NAME: _____	NAME: _____
ADDRESS: _____	ADDRESS: _____
PHONE #: _____	PHONE #: _____

YOU ARE REQUIRED TO SUBMIT TWO SEPARATE CHECKS & COPY OF THE PROPERTY TAX CARD AVAILABLE AT THE TAX OFFICE.

Building Inspection Fees Payable to BOROUGH OF PALISADES PARK.

- A. For one family homes, Condominiums,: \$50.00 CK # : _____
- B. For two family homes: \$100.00 CK # : _____
- C. For multiple dwellings: First Unit : \$100.00
Each additional unit: \$50.00 CK # : _____
- D. Business up to 10,000 sq. ft.: \$500.00 CK # : _____
Each additional 1,000 sq. ft.: \$100.00 _____
- E. Reinsertion fee (per Occupancy) \$50.00 CK # : _____

- Fire safety inspection fee of \$100.00 one /two family, all others \$100.00 per unit payable to PALISADES PARK FIRE PREVENTION

This document serves notice that based on a general inspection of the visible parts of the building, there are no imminent hazard; this dwelling is approved for continued occupancy.

Certificate of smoke detectors and carbon monoxide compliance.

DEPARTMENT OF BUILDINGS
AFFIDAVIT FOR ONE & TWO FAMILY DWELLINGS.

Date:

Block:

Lot:

Property Address:

Purchaser:

Telephone #:

Purchaser Address:

Owner Occupied: ()

Non Owner Occupied: ()

1. I am about to enter into possession or ownership of the premises described above.
2. I hereby acknowledge that I am aware that the premises are to be used in a manner which is consistent with all local and state laws.
3. I am also aware that local ordinance imposes a limit on the number of families, and other persons who can occupy these premises.
4. I hereby agree to comply with the requirements of said limitations.
5. I am signing this affidavit in order to induce the building department to issue the appropriate Certificate of Continued Occupancy and I am aware that this statement is relied upon by that department.
6. I hereby certify that the statements herein are true. I am aware that if any of the foregoing statements made by me are willfully false, that I am subject to punishment.

You must submit this statement signed and notarized before a Continued Certificate of Occupancy can be issued.

PURCHASER SIGNATURE:

NOTARY SIGNATURE:

DATE

**APPLICATION AND
CERTIFICATION IN LIEU OF
INSPECTION FOR CERTIFICATE
OF SMOKE DETECTOR AND
CARBON MONOXIDE ALARM
AND PORTABLE FIRE
EXTINGUISHER COMPLIANCE**

**Borough of Palisades Park
Bergen County, N.J. 07650**

**BUREAU OF FIRE PREVENTION
275 BROAD AVENUE
PALISADES PARK, NEW JERSEY 07650
PHONE: (201) 585-4132
FAX: (201) 944-8059**



DWELLING LOCATION: _____ BLOCK: _____ LOT: _____
(NOT MAILING ADDRESS)
STREET: _____

*NOTE: ALL BOXES MUST BE CHECKD IN ORDER FOR CERTIFICATION TO BE VALID

SMOKE DETECTORS SHALL BE LOCATED:

- A. IF CONSTRUCTED PRIOR TO 1977 ON EACH LEVEL OF DWELLING AND WITHIN 10 FEET OF SLEEPING AREAS. (DETECTORS MAY BE BATTERY POWERED.) DETECTORS MUST BE MOUNTED ON THE CEILING OR ON THE WALL WITHIN 6" OF THE CEILING.
- B. IF CONSTRUCTED BETWEEN 1977 AND 1989 ON EACH LEVEL OF DWELLING AND WITHIN 10 FEET OF SLEEPING AREAS. (DETECTORS MUST BE 110V) DETECTORS MUST BE MOUNTED ON THE CEILING OR ON THE WALL WITHIN 6" OF THE CEILING.
- C. IF CONSTRUCTED AFTER 1990 ON EACH LEVEL OF DWELLING, INSIDE OF EACH SLEEPING ROOM AND WITHIN 10 FEET OF SLEEPING AREAS. (DETECTORS MUST BE 110V WITH BATTERY BACK-UP, AND BE INTERCONNECTED.) DETECTORS MUST BE MOUNTED ON THE CEILING OR ON THE WALL WITHIN 6" OF THE CEILING.
- D. BATTERIES IN ALL SMOKE DETECTORS SHALL BE TESTED ONCE A MONTH AND CHANGED ONCE A YEAR TO ASSURE PROPER OPERATION.
- E. ALL SMOKE DETECTORS WITH A MANUFACTURE DATE GREATER THAN 10 YEARS MUST BE REPLACED.

_____ DETECTOR DATE OF MANUFACTURE

CARBON MONOXIDE DETECTORS SHALL BE LOCATED:

- A. WITHIN 10 FEET OF ALL SLEEPING AREAS.
- B. ALL CARBON MONOXIDE DETECTORS WITH A MANUFACTURE DATE GREATER THAN 5 YEARS MUST BE REPLACED.

_____ DETECTOR DATE OF MANUFACTURE

ALL SMOKE DETECTORS ARE IN WORKING ORDER. CARBON MONOXIDE ALARM(S) IN WORKING ORDER

FIRE EXTINGUISHER IS THE CORRECT SIZE, IS PROPERLY MOUNTED, AND IS LOCATED WITHIN 10 FEET OF THE KITCHEN

MAIL CERTIFICATE TO: _____ PHONE #: _____

_____ FAX #: _____

_____ ZIP: _____

EMAIL CERTIFICATE TO: _____

CONTACT PERSON: _____ PHONE #: _____ CLOSING DATE: _____

I _____ HEREBY CERTIFY THAT AT THE ABOVE REFERENCED LOCATION, OF WHICH I AM THE OWNER, AGENT, TENANT, OR NJ LICENSED ELECTRICIAN, THE FOLLOWING ITEMS HAVE BEEN INSTALLED, MAINTAINED, AND CHECKED FOR PROPER OPERATION IN ACCORDANCE WITH N.J.A.C. 5:70-2.3, N.J.A.C. 5:70-4.19, N.J.A.C. 5:70-3,907.21, N.J.A.C. 5:70-3,703.2.3, AND NFPA 72.

DATE

APPLICANT SIGNATURE

PRINTED NAME

CCO/Certificate of Smoke Detector and Carbon Monoxide Alarm Compliance Requirements

In accordance with N.J.A.C 5:70-3,907.21 and NFPA 72

1. SMOKE DETECTORS SHALL BE LOCATED:

- a. If constructed prior to 1977 on each level of dwelling and within 10 feet of sleeping areas. (Detectors may be battery powered.) Detectors must be mounted on the ceiling or on the wall within 6" of the ceiling.
- b. If constructed between 1977 and 1989 on each level of dwelling and within 10 feet of sleeping areas. (Detectors must be 110V) Detectors must be mounted on the ceiling or on the wall within 6" of the ceiling.
- c. If constructed after 1990 on each level of dwelling, Inside of each sleeping room and within 10 feet of sleeping areas. (Detectors must be 110V with battery back-up, and be interconnected.) Detectors must be mounted on the ceiling or on the wall within 6" of the ceiling.
- d. Single station smoke detectors shall be tested or inspected once a week and cleaned and batteries changed once a year to assure proper operation.
- e. All smoke detectors with a manufacture date greater than 10 years must be replaced.

2. CARBON MONOXIDE DETECTORS SHALL BE LOCATED:

- a. Within 10 feet of all sleeping areas.
- b. All carbon monoxide detectors with a manufacture date greater than 5 years must be replaced.

3. Apartment Entry Doors

- a. All doors separating dwelling units from common hallways must be self closing and self latching.

4. Fire Extinguisher

- a. One and two family houses must have a 10 pound type ABC fire extinguisher within 10 feet of each kitchen.